

Harley-Davidson

2015 Harley-Davidson Street® Harley-Davidson Street® 750									
MILES (in thousands)	1	5	10	15	20	25	30	35	40
KILOMETERS (in thousands)	1.6	8	16	24	32	40	48	56	64
Engine oil and filter Replace <u>1</u>	✓	✓	✓	✓	✓	✓	✓	✓	✓
Front tire Check pressure, inspect tread <u>1</u>	✓	✓	✓	✓	✓	✓	✓	✓	✓
Front brake pads and discs Check for wear	✓	✓	✓	✓	✓	✓	✓	✓	✓
Front brake caliper Inspect and lubricate pins and bushings <u>2</u>	✓	✓	✓	✓	✓	✓	✓	✓	✓
Front brake system Check for leaks, contact or abrasion <u>1</u>	✓	✓	✓	✓	✓	✓	✓	✓	✓
Repair as necessary <u>2</u>	✓	✓	✓	✓	✓	✓	✓	✓	✓
Front brake fluid Check level in sight glass	✓	✓	✓	✓	✓	✓	✓	✓	✓
Flush and replace fluid <u>2</u>	Flush system and replace DOT 4 hydraulic brake fluid e								
Throttle cables Check and adjust <u>2</u>	✓	✓	✓	✓	✓	✓	✓	✓	✓
Lubricate <u>2</u>	✓	✓	✓	✓	✓	✓	✓	✓	✓
Brake and clutch controls Check and adjust <u>2</u>	✓	✓	✓	✓	✓	✓	✓	✓	✓
Lubricate <u>2</u>	✓	✓	✓	✓	✓	✓	✓	✓	✓
Front fork Rebuild and replace fork oil <u>2</u>									
Steering head bearings Adjust <u>2</u>	✓				✓				✓
Lubricate <u>2</u>					✓				✓
Radiator Clean	✓	✓	✓	✓	✓	✓	✓	✓	✓
Cooling system Check for leaks and check clamps for tightness	✓	✓	✓	✓	✓	✓	✓	✓	✓
Check coolant level	✓	✓	✓	✓	✓	✓	✓	✓	✓
Check coolant freeze point <u>2</u>	✓	✓	✓	✓	✓	✓	✓	✓	✓
Replace coolant <u>2</u>	Replace fluid every 48,000 k								
Fuel lines and fittings Check for leaks, contact or abrasion <u>1</u>	✓	✓	✓	✓	✓	✓	✓	✓	✓
Repair as necessary <u>2</u>	✓	✓	✓	✓	✓	✓	✓	✓	✓

2015 Harley-Davidson Street® Harley-Davidson Street® 750

MILES (in thousands) KILOMETERS (in thousands)	1 1.6	5 8	10 16	15 24	20 32	25 40	30 48	35 56	40 64
Jiffy stand Check and lubricate 2, 3	✓	✓	✓	✓	✓	✓	✓	✓	✓
Shift and brake levers Clean and lubricate, inspect for wear 2					✓				✓
Rear fork bearing Inspect 2					✓				✓
Drive belt and sprockets Inspect, adjust belt 2	✓	✓	✓	✓	✓	✓	✓	✓	✓
Rear tire Check pressure, inspect tread 1	✓	✓	✓	✓	✓	✓	✓	✓	✓
Rear shock absorber bushings Inspect for wear and cracks 2					✓				✓
Rear brake pads and disc Check for wear 1	✓	✓	✓	✓	✓	✓	✓	✓	✓
Rear brake system Check for leaks, contact or abrasion 1	✓	✓	✓	✓	✓	✓	✓	✓	✓
Repair as necessary 2	✓	✓	✓	✓	✓	✓	✓	✓	✓
Rear brake caliper Inspect and lubricate pins and bushings 2	✓	✓	✓	✓	✓	✓	✓	✓	✓
Rear brake fluid Check level in sight glass	✓	✓	✓	✓	✓	✓	✓	✓	✓
Flush and replace fluid 2	Flush system and replace DOT 4 hydraulic brake fluid e								
Exhaust system Check for leaks, cracks and loose or missing fasteners or exhaust shields 1, 3	✓	✓	✓	✓	✓	✓	✓	✓	✓
Repair as necessary 2	✓	✓	✓	✓	✓	✓	✓	✓	✓
Air cleaner filter Inspect, service as required 3	✓	✓	✓	✓	✓	✓	✓	✓	✓
Fuel cap lock Lubricate 3	✓	✓	✓	✓	✓	✓	✓	✓	✓
Valve lash Inspect, adjust if necessary 2, 4				✓			✓		
Battery Check and clean 1	Check battery, terminal torque and clean connec								
Spark plugs Replace	Replace every two years or every 48,000 km (30,000 mi), whichever								
Electrical equipment and switches Check operation	✓	✓	✓	✓	✓	✓	✓	✓	✓
Road test Verify component and system functions	✓	✓	✓	✓	✓	✓	✓	✓	✓

NOTES

1. Perform annually or at specified intervals, whichever comes first.
2. Should be performed by an authorized Harley-Davidson dealer, unless you have the proper tools, service data and are mecl
3. Perform maintenance more frequently in severe riding conditions (such as extreme temperatures, dusty environments, mot rough roads, long storage conditions, short runs, heavy stop/go traffic or poor fuel quality).
4. Could vary with frequency of operation and riding style.