

|               |       |              |  |     |
|---------------|-------|--------------|--|-----|
| 2008 Rocker C | 4,851 | 816-830-6033 |  | mac |
|---------------|-------|--------------|--|-----|

| Item                | Description   | Qty |
|---------------------|---|-----|
| 34822-08            | Timken Bearing Sleeve   | 1   |
| 1106-0074           | SPACER SPRKT SHAFT 11887  | 1   |
| 0924-0108           | Left Crank Case Main Bearings   | 1   |
| Oil -Primary        | Primary Oil, qt   |     |
| Oil Filter Twin Cam | Twin Cam Chrome Oil Filter  | 2   |
| Oil - Motor 20/50   | HD 20/50 Motor Oil for the first 50 miles then drained  | 3   |
| Oil-Amsoil 20/50    | Amsoil, 20/50 Synthetic, Qt   | 3   |
| 1020-1851           | THUNDERMAX ECM W/AUTOTUNE NON-TBW<br>YOUR NEW THUNDERMAX WAVE TUNER WILL BE AUTO<br>TUNING YOUR BIKE CONSTANTLY. IT IS IMPORTANT TO<br>USE A QUALITY HIGH CRANKING AMP BATTERY AT ALL<br>TIMES. NEVER PUT ANY ADDITIVES IN YOUR GAS TAN<br>BECAUSE IT COULD RUIN YOUR O2 SENSORS THAT<br>SEND SIGNALS TO THE TUNER. | 1   |
| 17997-99A           | Harley Davidson Adjustable Push rod kit   | 1   |
| 1861-0694           | Bungs 02 Weld in 18MM   | 1   |
| 1861-0560           | BUNGS 02 WELD IN 18MM   | 1   |
| Primary ST          | Primary Gasket Softail  | 1   |
| Labor               | Disassemble motor and new heads, weld in bungs in exhaust,<br>assemble and adjust. Test ride, tune, drain oil and oil change  | 18  |